

Issue date March 1, 2015

Reviewed date November 1, 2023

Safety Data Sheet

SDS ID# 3090

Section 1. IDENTIFICATION

1.1. Product identifier

Product form : Mixture

Product name : Propane (0.0001%-1.1%) in Air (Oxygen 20.9% bal. Nitrogen)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Calibration gas/Bumptest gas/Function test gas

1.3. Details of the supplier of the safety data sheet

Intermountain Specialty Gases

21913 Cobalt Ave.

Caldwell, Idaho 83605

Telephone 1-208-585-5829 or Toll free 1-800-552-5003

www.isgases.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

Section 2. HAZARDS INDENTIFICATION

2.1. Classification of the substance or mixture

Classification : GASES UNDER PRESSURE - Compressed gas

2.2. Label elements

Hazard pictograms



Signal word : WARNING

Hazard statements : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

: CGA-HG24 - MAY SUPPORT COMBUSTION

: OSHA - PG01 - DO NOT REMOVE THIS PRODUCT LABEL

Precautionary statements

[General] : Read and follow all Safety Data Sheets (SDS's) before use. Read label before use. Keep

out of reach of children. If medical advice is needed, have a product container or label at

hand. Use equipment rated for cylinder pressure.



[Prevention] : P202 - Do not handle until all safety precautions have been read and understood

: P271+P403- Use only outdoors or in a well-ventilated area

[Response] : P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

[Storage] : CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

[Disposal] : Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

No data available

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%
Nitrogen	(CAS No) 7727-37-9	75.4 - 80.4999
Oxygen	(CAS No) 7782-44-7	19.5 - 23.5
Propane	(CAS No) 74-98-6	0.0001 - 1.1

Section 4. FIRST AID MEASURES

4.1. Description of first aid measures

General : IF exposed or concerned: Get medical advice/attention.

Inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If

breathing has stopped, give artificial respiration or oxygen by trained personnel. If

victim feels unwell, seek medical advice.

Skin contact : Immediately flush with copious amount of water for at least 15 minutes.

Eye contact : Immediately flush with copious amount of water for at least 15 minutes.

Ingestion : Ingestion is not considered a potential route of exposure, refer to the inhalation

section.

4.2. Most important symptoms/effects, acute and delayed

Acute

Inhalation : Adverse effects not expected from this product.

Skin contact : Contact with rapidly expanding gas may cause burns or frostbite. Eye contact : Contact with rapidly expanding gas may cause burns or frostbite.

Ingestion : Ingestion is not considered a potential route of exposure, refer to the inhalation

section.

Frostbite : Thaw frosted parts with lukewarm water. Do not rub affected areas. Get immediate

medical advice/attention.

EN (English US) SDS ID# 3090 Page 2 of 9



Symptoms/injuries upon intravenous

administration

: Symptoms of overexposure are dizziness, headache, tiredness, nausea,

unconsciousness, cessation of breathing.

Chronic symptoms : Adverse effects not expected from this product.

Delayed : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If victim feels unwell, seek medical advice. If breathing is difficult, give artificial respiration or oxygen by trained personnel.

Section 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : None known

5.2. Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing

risk of burns and injuries.

Reactivity : None known.

5.3. Advice for fire-fighters

Firefighting instructions : In case of fire: Evacuate all personnel from the danger area. Stop the leak and flow

of gas before extinguishing fire, if safe to do so. If this is not possible, withdraw from area and allow fire to burn. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Let the fire burn. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Exercise

caution when fighting any chemical fire.

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing

Apparatus, SCBA) for fire fighters. Do not enter fire area without proper protective

equipment, including respiratory protection.

Section 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

6.1.1. For non -emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of

adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying

areas. Keep upwind.

6.1.12. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing

Apparatus) for fire fighters. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate and limit access. Ventilate area. See information above "For non-

emergency personnel".

6.2. Methods and material for containment and cleaning up

For containment : Immediately contact emergency personnel. Try to stop gas leak if safe to do so.

EN (English US) SDS ID# 3090 Page 3 of 9



Methods for cleaning up

:Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Precautions for safety handling : Pressurized container: Do not pierce or burn, even after use. Use equipment rated

for cylinder pressure. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Protect cylinders from physical damage; do

not drag, roll, slide, or drop.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : None known.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Store locked up. Keep

containers closed when not in use. Protect cylinder from physical damage. Store and use away from heat, sparks, open flame or any other ignition source. Store in well

ventilated area.

Incompatible products : None known. Incompatible materials : None known.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Nitrogen (7727-37-9)				
OSHA PEL		Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV
ppm	mg/m³	(as of 4/26/13)	(as of 4/26/13)	
		8-hour TWA	up to 10-hour TWA	8-hour TWA
		(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling
Not established	Not established	Not established	Not established	Simple asphyxiant

Oxygen (7782-44-7)					
OSHA PEL		Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV	
ppm	mg/m³	(as of 4/26/13)	(as of 4/26/13)		
		8-hour TWA	up to 10-hour TWA	8-hour TWA	
		(ST) STEL	(ST) STEL	(ST) STEL	
		(C) Ceiling	(C) Ceiling	(C) Ceiling	

There are no specific exposure limits for Nitrogen. Nitrogen is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.

Propane (74-98-6)				
OSHA PEL	Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV	



ppm mg/m³	(as of 4/26/13)	(as of 4/26/13)		
	3	8-hour TWA	up to 10-hour TWA	8-hour TWA
	(ST) STEL	(ST) STEL	(ST) STEL	
	(C) Ceiling	(C) Ceiling	(C) Ceiling	
1,000 ppm 1,800 mg/m ³	1,000 ppm	1,000 ppm	1,000 ppm	

8.2. Appropriate engineering controls

Engineering measures/controls

: Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly check for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may me released. Consider work permit system e.g. for maintenance activities.

8.3. Individual protection measures

Hand protection : Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection. Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection. Skin and body protection : Wear suitable protective clothing, e.g.-Lab coats, coveralls or flame resistant clothing.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved

standard if a risk assessment indicates this is necessary.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section

13 for specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Exposure controls

Appearance : Clear, colorless gas.

Physical state : Gas
Color : Colorless

Odor : No data available
Odor threshold : No data available
pH : No data available
Freezing point : No data available
Flash point : No data available
Evaporation rate : No data available

Flammability (solid, gas) : Not Flammable - not combustible

Upper flammability : 9.5% Lower flammability : 2.1%

Relative density : No data available
Solubility : No data available
Partition coefficient : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : Not applicable

EN (English US) SDS ID# 3090 Page 5 of 9



Molecular weight (grams)

Boiling point

Vapor pressure

Vapor density at 20°C

Relative gas density

Critical Temperature

Propane	Oxygen	Nitrogen	
44.09	32.00	28.013	
-42.04 °C	-182.9 °C	-196 °C	
8.39 bar	Above critical	Above critical	
@20°C	temperature	temperature	
1.55	1.11	0.97	
1.858 kg/m³ @ 20 °C	1.331	1.153	
96.67 °C	-118.6 °C	-146.9 °C	

Section 10. STABILITY AND REACTIVITY

10.1. Reactivity

No reactivity hazard other than the effects described below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.4. Conditions to avoid

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

None known

Section 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Nitrogen (7727-37-9)

LC50 inhalation rat (ppm) 410,000 ppm/4 hours

Oxygen (7782-44-7)

LC50 inhalation rat (ppm) 400,000 ppm/4 hours

Propane (74-98-6)

LC50 inhalation rat (mg/L) 658 mg/L / 4 hours

11.1. Information on routes of exposure

Inhalation : Adverse effects not expected from this product
Skin contact : Adverse effects not expected from this product
Eye contact : Adverse effects not expected from this product

EN (English US) SDS ID# 3090 Page 6 of 9



Ingestion : Ingestion is not considered a potential route of exposure

11.2. Symptoms related to physical, chemical and toxicological characteristics

Symptoms : No information available

11.3. Delayed and immediate effects

Skin corrosion/irritation : Contact with rapidly expanding gas may cause burns or frostbite.

Serious eye damage/irritation : Contact with rapidly expanding gas may cause burns or frostbite.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Developmental Toxicity : Not classified Specific target organ toxicity (single : Not classified

exposure)

Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Not applicable for gases and gas-mixtures

11.4. Carcinogenic effects

The components of this material are not found on the following lists: FEDERAL OSHA Z LIST, NTP AND IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

Section 12. ECOLOGICAL INFORMATION

12.1. Aquatic Toxicity

Ecology - general : No ecological damage caused by this product

12.2. Persistence and degradability

No information available for the product

12.3. Bioaccumulative potential

Propane (74-98-6)

Partition coefficient 2.3

12.4. Mobility in soil

No information available for the product

12.5. Other

No information available for the product

Section 13. DISPOSAL CONSIDERATIONS

13.1. Disposal methods

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



Section 14. TRANSPORATION INFORMATION

	US DOT	TDG	IMDG	IATA
UN#	UN 1956	UN 1956	UN 1956	UN 1956
Proper shipping name	Compressed gas, n.o.s. (Nitrogen, Oxygen)			
Transport hazard class(es)	2.2 NON-FLAMMABLE GAS	2.2 NON-FLAMMABLE GAS	2.2 NON-FLAMMABLE GAS	2.2 NON-FLAMMABLE GAS
Packing group	-	-	-	-
Environment	No.	No.	No.	No.

Section 15. REGULATORY INFORMATION

15.1. US Federal regulations

SARA 311/312 hazard categories

Acute Health : No
Chronic Health : No
Fire : No
Pressure : Yes
Reactive : No

SARA Title III Notifications and Information: None known

This product does not contain toxic chemicals subject to reporting requirements of section 313 of the Emergency planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

SARA 311/312 Sudden Release of Pressure Hazard

15.2. US State regulations

Nitrogen (007727-37-9)

- U.S. Massachusetts Right To Know List
- U.S. Minnesota Right To Know Hazardous Substance List
- U.S. New Jersey Right To Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right To Know) List

Oxygen (007782-44-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right To Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right To Know) List

Propane (74-98-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right To Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right To Know) List



Section 16. OTHER INFORMATION

Date of issue/Date of revision 11/1/2023
Revision Note : Initial release

Hazardous Material Information System (USA)

Hazard Scale : 0 = Minimal/ 1 = Slight/ 2 = Moderate/ 3 = Serious/ 4 = Severe

Health : 0
Fire : 0
Physical hazards : 3

Key/Legend

SARA Superfund Amendments and Reauthorization Act
OSHA Occupational Safety and Health Administration

DOT Department of Transportation
TSCA Toxic Substance Control Act
NTP National Toxicology Program

ACGIH American Conference of Governmental Industrial Hygienists

PEL Permissible Exposure Limit
STEL Short Term Exposure Limit
TLV Threshold Limit Value

TDG Transportation of Dangerous Goods

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

TWA Time Weighted Average

Prop Proposition

ATE Acute Toxicity Estimate

DISCLAIMER OF EXPRESSED AND IMPLIED WARRATIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose (s).

EN (English US) SDS ID# 3090 Page 9 of 9