

Issue date	March 1, 2015	Safety Data Sheet
Reviewed date November 1, 2023		023
		SDS ID# 4047
Section 1. IDENT		
Product form		: Mixture
Product name		: Carbon Monoxide (0.0001%-0.0999%); Pentane (0.0001%-0.75%); Oxygen (19.5%-23.5%) in Nitrogen
	entified uses of the	e substance or mixture and uses advised against
Product use		: Calibration gas/Bumptest gas/Function test gas
1.3. Details of th	e supplier of the s	safety data sheet
Intermountain Sp 21913 Cobalt Ave Caldwell, Idaho 8 Telephone 1-208 www.isgases.cor	e. 3605 -585-5829 or Tol	ll free 1-800-552-5003
	elephone numbe	
Emergency numb	ber	: CHEMTREC: 1-800-424-9300
Section 2. HAZA	RDS INDENTIFICA	TION
	n of the substance	
Classification		: GASES UNDER PRESSURE - Compressed gas
2.2. Label eleme	nts	
Hazard pictograr	ns	
Signal word		: WARNING
Hazard statemer	nts	: H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED : CGA-HG24 - MAY SUPPORT COMBUSTION : OSHA - PG01 - DO NOT REMOVE THIS PRODUCT LABEL
Precautionary st	atements	
[General]		: Read and follow all Safety Data Sheets (SDS's) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have a product container or label at hand. Use equipment rated for cylinder pressure.



: P271+P403- Use only outdoors or in a well-ventilated area

[Response]	: P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. : P313 - Get medical advice/attention.
[Storage]	: CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
[Disposal]	: Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

No data available

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%
Nitrogen	(CAS No) 7727-37-9	75.6501 - 80.4998
Oxygen	(CAS No) 7782-44-7	19.5 - 23.5
Pentane	(CAS No) 109-66-0	0.0001 - 0.75
Carbon Monoxide	(CAS No) 630-08-0	0.0001 - 0.0999

Section 4. FIRST AID MEAS	URES
4.1. Description of first aid	measures
General	: IF exposed or concerned: Get medical advice/attention.
Inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. If
	breathing has stopped, give artificial respiration or oxygen by trained personnel. If victim feels unwell, seek medical advice.
Skin contact	: Immediately flush with copious amount of water for at least 15 minutes.
Eye contact	: Immediately flush with copious amount of water for at least 15 minutes.
Ingestion	: Ingestion is not considered a potential route of exposure, refer to the inhalation
	section.
4.2. Most important symp	toms/effects, acute and delayed
Acute	
Inhalation	: Adverse effects not expected from this product.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Ingestion	: Ingestion is not considered a potential route of exposure, refer to the inhalation section.
Frostbite	: Thaw frosted parts with lukewarm water. Do not rub affected areas. Get immediate
EN (English US)	medical advice/attention#.4047 Page 2 of 1



Symptoms/injuries upon intravenous administration	: Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing.
Chronic symptoms	: Adverse effects not expected from this product.
Delayed	: Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If victim feels unwell, seek medical advice. If breathing is difficult, give artificial respiration or oxygen by trained personnel.

Section 5. FIREFIGHTING MEASURES 5.1. Extinguishing media	
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None known
5.2. Special hazards arising from the s	ubstance or mixture
Fire hazard	: The product is not flammable
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing
	risk of burns and injuries.
Reactivity	: None known.
5.3. Advice for fire-fighters	
Firefighting instructions	: In case of fire: Evacuate all personnel from the danger area. Stop the leak and flow of gas before extinguishing fire, if safe to do so. If this is not possible, withdraw from area and allow fire to burn. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Let the fire burn. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus, SCBA) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

Section 6. ACCIDENTAL RELEASE	MEASURES			
6.1. Personal precautions, protective equipment and emergency procedures				
General measures	: Ensure adequate ventilation.			
6.1.1. For non -emergency perso	nnel			
Protective equipment	: Wear protective equipment consistent with the site emergency plan.			
Emergency procedures	: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.			
6.1.12. For emergency responder	rs			
Protective equipment	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.			
Emergency procedures	: Evacuate and limit access. Ventilate area. See information above "For non- emergency personnel".			
6.2. Methods and material for co				
Enr(English US)	: Immediately contact emergency personnel. Try to stop gas leak if safe to do so. SDS ID# 4047			



Methods for cleaning up	:Dispose of content and/or container in accordance with local, regional, national,
	and/or international regulations.
Section 7. HANDLING AND STORA	GE
7.1. Precautions for safe handling	
Precautions for safety handling	: Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Protect cylinders from physical damage; do
	not drag, roll, slide, or drop.
Hygiene measures	
	not drag, roll, slide, or drop. : Do not eat, drink or smoke when using this product.
	not drag, roll, slide, or drop. : Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, inc	not drag, roll, slide, or drop. : Do not eat, drink or smoke when using this product. cluding any incompatibilities
7.2. Conditions for safe storage, inc Technical measures	not drag, roll, slide, or drop. : Do not eat, drink or smoke when using this product. cluding any incompatibilities : None known. : Do not expose to temperatures exceeding 52°C (125°F). Keep containers closed

Nitrogen (7727-37-9)			
OSHA PEL		Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV
	mg/m ³	(as of 4/26/13)	(as of 4/26/13)	
222		8-hour TWA	up to 10-hour TWA	8-hour TWA
ppm		(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling
Not established	Not established	Not established	Not established	Simple asphyxiant
Notestablished				
Oxygen (7782-44-7)				
OSHA PEL		Cal/OSHA PEL	NIOSH REL	

OSHA PEL			NIOSH REL	ACGIH 2015 TLV
	··· - /··· ³	(as of 4/26/13)	(as of 4/26/13)	
222		8-hour TWA	up to 10-hour TWA	8-hour TWA
ppm	mg/m³	(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling

There are no specific exposure limits for Nitrogen. Nitrogen is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.

Pentane (109-66-0)				
OSHA PEL		Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV
		(as of 3/1/1989)	(as of 4/26/13)	
EN (English ปร)		8-hour TWA SDS ID# 4047	up to 10-hour TWA	8-hour TWA Page 4 of 1



ρμιι	mg/m	(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling
1,000 ppm	$2,950 \text{ mg/m}^3$	600 ppm	120 ppm	600 ppm
1,000 ppm	2,950 mg/m	750 ppm [15 min]	(IDLH): 1,500 ppm	
			(C) 610 ppm [15-min]	
Carbon Monoxide (6	30-08-0)			
OSH	A PEL	Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV
		(as of 4/26/13)	(as of 4/26/13)	
		8-hour TWA	up to 10-hour TWA	8-hour TWA
n nm	mg/m ³	(ST) STEL	(ST) STEL	(ST) STEL
ppm		(C) Ceiling	(C) Ceiling	(C) Ceiling
			(IDHL) Immediately Dangerous	
			to Life or Health	
				<u>a -</u>
50 nnm	$EE ma/m^3$	25 ppm	35 ppm	25 ppm

(C) 200 ppm

 55 mg/m^3

Engineering measures/controls

50 ppm

: Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly check for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may me released. Consider work permit system e.g. for maintenance activities.

(C) 200 ppm (IDLH) 1,200 ppm

8.3. Individual protection measures	
Hand protection	: Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.gLab coats, coveralls or flame resistant clothing.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved
	standard if a risk assessment indicates this is necessary.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section
	13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection

Section 9. PHYSICAL AND CI	HEMICAL PROPERTIES	
9.1. Exposure controls		
Appearance	: Clear, colorless gas.	
Physical state	: Gas	
Color	: Colorless	
Odor	: Slight gasoline type odor	
Odor threshold	: No data available	
рН	: No data available	
Ereezing point EN (English US)	: No data available SDS ID# 4047	Page 5 of 10



Flash point	: No da
Evaporation rate	: No da
Flammability (solid, gas)	: Not F
Upper flammability	: 7.8%
Lower flammability	: 1.5%
Relative density	: No da
Solubility	: No da
Partition coefficient	: No da
Auto-ignition temperature	: No da
Decomposition temperature	: No da
Viscosity	: Not a
-	

No data available

- No data available
- : Not Flammable not combustible
- : 7.8% (Pentane)
- : 1.5% (Pentane)
- : No data available
- : Not applicable

	Carbon Monoxide	Oxygen	Nitrogen	Pentane	
Molecular weight (grams)	58.12	32.00	28.013	72.14	
Boiling point	-0.5 °C	-182.9 °C	-196 °C	36 °C	
Vapor pressure	2200 hPa @ 20	Above critical	Above critical	1100 hPa	
	°C	temperature	temperature	@38°C	
Vapor density at 20°C	2.11	1.11	0.97	2.5	
Relative gas density	2.52 @ 15 °C	1.331	1.153	3.228 kg/m ³ @ 15 °C	
Critical Temperature	152.03 °C	-118.6 °C	-146.9 °C	°C	

Section 10. STABILITY AND REACTIVITY

10.1. Reactivity

No reactivity hazard other than the effects described below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.4. Conditions to avoid

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

410,000 ppm/4h

Section 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Nitrogen (7727-37-9)

LC50 inhalation rat (ppm)



Oxygen (7782-44-7)	
LC50 inhalation rat (ppm)	400,000 ppm/4h
Pentane (109-66-0)	
LC50 inhalation Vapor rat (ppm)	364 g/m3 /4 hours
Carbon Monoxide (630-08-0)	
LC50 inhalation rat (ppm)	3,760 ppm/1h
LC50 inhalation rat (ppm)	1,807 ppm/4h
	1,807 ppm/4m
11.1 Information on routes of owners	
11.1. Information on routes of exposu	
Inhalation	: Adverse effects not expected from this product
Skin contact	: Adverse effects not expected from this product
Eye contact	: May cause irritation.
Ingestion	: Ingestion is not considered a potential route of exposure
11.2. Symptoms related to physical, ch	nemical and toxicological characteristics
Symptoms	: Not classified
11.3. Delayed and immediate effects	
Skin corrosion/irritation	: Contact with rapidly expanding gas may cause burns or frostbite.
Serious eye damage/irritation	: Contact with rapidly expanding gas may cause burns or frostbite.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Genetic changes observed in mammalian cell assay systems at exposures of 1,500
Gennicen mutagementy	
A A A A	to 2,500 ppm of carbon monoxide for 10 minutes.
Carcinogenicity	: Not classified
Reproductive toxicity	: Category 1A. Overexposure to carbon monoxide may decrease the likelihood of
	successful pregnancy. In rats treated with carbon monoxide, the rate of successful
	pregnancy in the control group was 100% whereas the rest of successful pregnancy in
	animals treated with 30 and 90 ppm of carbon monoxide was 69% and 38%
	respectively.
Developmental Toxicity	Mice exposed to concentrations of carbon monoxide at 65 ppm and higher
	demonstrated doe-dependent effects on the fetus (increased mortality and
	decreased weight) with no signs of maternal toxicity. Offspring of rats exposed to 150
	ppm carbon monoxide had minor reductions in birth weight and persistent memory
	deficits which became more pronounced in adulthood.
Constitutor and a reason to visitu (single	: Not classified
Specific target organ toxicity (single	
exposure)	
Specific target organ toxicity (repeated	
exposure)	to 2,500 ppm of carbon monoxide for 10 minutes
	: Central vascular system (CVS), Lungs, Blood, Central nervous system (CNS)
Aspiration hazard	: Not classified
	Not applicable for gases and gas-mixtures



The components of this material are not found on the following lists: FEDERAL OSHA Z LIST, NTP AND IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

Section 12	. ECOLOGICAL INFORMATION		
42.4	at a manufacture		

Ecology - general

: No ecological damage caused by this product

12.2. Persistence and degradability

No information available for the product

12.3. Bioaccumulative potential	
Pentane (109-66-0)	
LogP _{ow}	3.45
BCF	171
Potential	low

12.4. Mobility in soil

No information available for the product

12.5. Other

No information available for the product

Section 13. DISPOSAL CONSIDERATIONS

13.1. Disposal methods

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14. TRANSPORATION INFORMATION

	US DOT	TDG	IMDG	ΙΑΤΑ
UN #	UN 1956	UN 1956	UN 1956	UN 1956
Proper shipping name	Compressed gas, n.o.s. (Nitrogen, Oxygen)			
Transport hazard class(es)	2.2 NON-FLAMMABLE GAS	2.2 NON-FLAMMABLE GAS	2.2 HON-FLAMMABLE GAS	2.2 NON-FLAMMABLE GAS
Packing group	-	-	-	-
Environment	No.	No.	No.	No.

Section 15. REGULATORY INFORMATION

15.1. US Federal regulations



Chronic Health	: Yes	
Fire	: No	
Pressure	: Yes	
Reactive	: No	
SARA Title III Notifications a	nd Information: None known	
This product does not cont	in toxic chemicals subject to reporting requirement	ts of section 313 of the Emergency planning
and Community Right-To-K	now Act (EPCRA) of 1986 and of 40 CFR 372.	
SARA 311/312	Sudden Release of Pressure Hazard	

15.2. US State regulations

DOT

Nitrogen (007727-37-9)
U.S Massachusetts - Right To Know List
U.S Minnesota - Right To Know Hazardous Substance List
U.S New Jersey - Right To Know Hazardous Substance List
U.S Pennsylvania - RTK (Right To Know) List
Oxygen (007782-44-7)
U.S Massachusetts - Right To Know List
U.S New Jersey - Right To Know Hazardous Substance List
U.S Pennsylvania - RTK (Right To Know) List
Pentane (109-66-0)
U.S Massachusetts - Right To Know List
U.S New Jersey - Right To Know Hazardous Substance List
U.S Pennsylvania - RTK (Right To Know) List
Carbon Monoxide (630-08-0)
U.S Massachusetts - Right To Know List
U.S New Jersey - Right To Know Hazardous Substance List
U.S Pennsylvania - RTK (Right To Know) List
U.S California Proposition 65 (Developmental)

Date of issue/Date of revision	11/1/2023
Revision Note	
Hazardous Material Information S	ystem (USA)
Hazard Scale	: 0 = Minimal/ 1 = Slight/ 2 = Moderate/ 3 = Serious/ 4 = Severe
Health	: 1
Fire	: 0
Physical hazards	: 3
Key/Legend	
SARA	Superfund Amendments and Reauthorization Act
OSHA	Occupational Safety and Health Administration

Occupational Safety and Health Administration Department of Transportation

TSCA Toxic Substance Control Act

National Toxicology Program SDS ID# 4047



ACGIH	American Conference of Governmental Industrial Hygienists
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TDG	Transportation of Dangerous Goods
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
TWA	Time Weighted Average
Prop	Proposition
ATE	Acute Toxicity Estimate

DISCLAIMER OF EXPRESSED AND IMPLIED WARRATIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose (s).