

Issue date March 1, 2015
Reviewed date November 1, 2023

Safety Data Sheet

SDS ID# 5000

Section 1. IDENTIFICATION

1.1. Product identifier

Product form : Mixture
Product name : Hydrogen Sulfide (0.0001%-0.05%) in Air (Oxygen 20.9% bal. Nitrogen)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Calibration gas/Bumptest gas/Function test gas

1.3. Details of the supplier of the safety data sheet

Intermountain Specialty Gases
21913 Cobalt Ave.
Caldwell, Idaho 83605
Telephone 1-208-585-5829 or Toll free 1-800-552-5003
www.isgases.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

Section 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification : GASES UNDER PRESSURE - Compressed gas

2.2. Label elements

Hazard pictograms



Signal word : WARNING

Hazard statements : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
: CGA-HG24 - MAY SUPPORT COMBUSTION
: OSHA - PG01 - DO NOT REMOVE THIS PRODUCT LABEL

Precautionary statements

[General] : Read and follow all Safety Data Sheets (SDS's) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have a product container or label at hand. Use equipment rated for cylinder pressure.

| | |
|--------------|--|
| [Prevention] | : P202 - Do not handle until all safety precautions have been read and understood : P271+P403- Use only outdoors or in a well-ventilated area |
| [Response] | : P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. |
| [Storage] | : CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F) |
| [Disposal] | : Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. |

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

No data available

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product Identifier | % |
|------------------|--------------------|-----------------|
| Nitrogen | (CAS No) 7727-37-9 | 76.45 - 80.4999 |
| Oxygen | (CAS No) 7782-44-7 | 19.5 - 23.5 |
| Hydrogen Sulfide | (CAS No) 7783-06-4 | 0.0001 - 0.05 |

Section 4. FIRST AID MEASURES

4.1. Description of first aid measures

| | |
|--------------|--|
| General | : IF exposed or concerned: Get medical advice/attention. |
| Inhalation | : Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, give artificial respiration or oxygen by trained personnel. If victim feels unwell, seek medical advice. |
| Skin contact | : Immediately flush with copious amount of water for at least 15 minutes. |
| Eye contact | : Immediately flush with copious amount of water for at least 15 minutes. |
| Ingestion | : Ingestion is not considered a potential route of exposure, refer to the inhalation section. |

4.2. Most important symptoms/effects, acute and delayed

Acute

| | |
|--------------|--|
| Inhalation | : Adverse effects not expected from this product. |
| Skin contact | : Contact with rapidly expanding gas may cause burns or frostbite. |
| Eye contact | : Contact with rapidly expanding gas may cause burns or frostbite. |
| Ingestion | : Ingestion is not considered a potential route of exposure, refer to the inhalation section. |
| Frostbite | : Thaw frosted parts with lukewarm water. Do not rub affected areas. Get immediate medical advice/attention. |

| | |
|---|---|
| Symptoms/injuries upon intravenous administration | : Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. |
| Chronic symptoms | : Adverse effects not expected from this product. |
| Delayed | : Adverse effects not expected from this product. |

4.3. Indication of any immediate medical attention and special treatment needed

If victim feels unwell, seek medical advice. If breathing is difficult, give artificial respiration or oxygen by trained personnel.

Section 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing media appropriate for surrounding fire. |
| Unsuitable extinguishing media | : None known |

5.2. Special hazards arising from the substance or mixture

| | |
|------------------|---|
| Fire hazard | : The product is not flammable |
| Explosion hazard | : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. |
| Reactivity | : None known. |

5.3. Advice for fire-fighters

| | |
|--------------------------------|---|
| Firefighting instructions | : In case of fire: Evacuate all personnel from the danger area. Stop the leak and flow of gas before extinguishing fire, if safe to do so. If this is not possible, withdraw from area and allow fire to burn. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Let the fire burn. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Exercise caution when fighting any chemical fire. |
| Protection during firefighting | : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus, SCBA) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection. |

Section 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|---|--|
| General measures | : Ensure adequate ventilation. |
| 6.1.1. For non-emergency personnel | |
| Protective equipment | : Wear protective equipment consistent with the site emergency plan. |
| Emergency procedures | : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind. |
| 6.1.12. For emergency responders | |
| Protective equipment | : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection. |
| Emergency procedures | : Evacuate and limit access. Ventilate area. See information above "For non-emergency personnel". |

6.2. Methods and material for containment and cleaning up

| | |
|-----------------|---|
| For containment | : Immediately contact emergency personnel. Try to stop gas leak if safe to do so. |
|-----------------|---|

Hydrogen Sulfide (0.0001%-0.05%) in Air (Oxygen 20.9% bal. Nitrogen)

Methods for cleaning up : Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Precautions for safety handling : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Protect cylinders from physical damage; do not drag, roll, slide, or drop.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : None known.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Store locked up. Keep containers closed when not in use. Protect cylinder from physical damage. Store and use away from heat, sparks, open flame or any other ignition source. Store in well ventilated area.

Incompatible products : None known.

Incompatible materials : None known.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Nitrogen (7727-37-9)

| OSHA PEL | | Cal/OSHA PEL | NIOSH REL | ACGIH 2015 TLV |
|------------------------|------------------------|--|---|--|
| ppm | mg/m ³ | (as of 4/26/13) | (as of 4/26/13) | 8-hour TWA (ST) STEL (C) Ceiling |
| | | 8-hour TWA (ST) STEL (C) Ceiling | up to 10-hour TWA (ST) STEL (C) Ceiling | |
| <i>Not established</i> | <i>Not established</i> | <i>Not established</i> | <i>Not established</i> | Simple asphyxiant |

Oxygen (7782-44-7)

| OSHA PEL | | Cal/OSHA PEL | NIOSH REL | ACGIH 2015 TLV |
|----------|-------------------|--|---|--|
| ppm | mg/m ³ | (as of 4/26/13) | (as of 4/26/13) | 8-hour TWA (ST) STEL (C) Ceiling |
| | | 8-hour TWA (ST) STEL (C) Ceiling | up to 10-hour TWA (ST) STEL (C) Ceiling | |

There are no specific exposure limits for Nitrogen. Nitrogen is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.

Hydrogen Sulfide (7783-06-4)

| OSHA PELs | Cal/OSHA PEL | NIOSH REL | ACGIH 2015 TLV |
|-----------|--------------|-----------|----------------|
| | | | |

Hydrogen Sulfide (0.0001%-0.05%) in Air (Oxygen 20.9% bal. Nitrogen)

| 8-hour Time Weighted Average (TWA) | Acceptable Ceiling Concentration | Acceptable maximum peak | | (as of 4/26/13) | (as of 4/26/13) | 2015 TLV |
|------------------------------------|----------------------------------|--|------------------|----------------------------------|--|--------------------------|
| | | Concentration | Maximum Duration | 8-hour TWA (ST) STEL (C) Ceiling | up to 10-hour TWA (ST) STEL (C) Ceiling IDLH | 8-hour TWA (ST) STEL (C) |
| 20 ppm | 50 ppm | 10 min once only if no other measurable exposure occurs. | 10 ppm | | 1 ppm | |
| | | | (ST) 15 ppm | (C) 10 ppm [10 min] | (ST) 5 ppm | |
| | | | (C) 20 ppm | IDLH - 100 ppm | | |

8.2. Appropriate engineering controls

Engineering measures/controls : Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly check for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may me released. Consider work permit system e.g. for maintenance activities.

8.3. Individual protection measures

Hand protection : Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.
 Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
 Skin and body protection : Wear suitable protective clothing, e.g.-Lab coats, coveralls or flame resistant clothing.
 Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
 Thermal hazard protection : None necessary during normal and routine operations.
 Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
 Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Exposure controls

Appearance : Clear, colorless gas.
 Physical state : Gas
 Color : Colorless
 Odor : Rotten eggs: Sulfide-like
 Odor threshold : 0.13 ppm (Hydrogen sulfide)
 pH : No data available
 Freezing point : No data available
 Flash point : No data available
 Evaporation rate : No data available
 Flammability (solid, gas) : Not Flammable - not combustible
 Upper flammability : Not Flammable - not combustible
 Lower flammability : Not Flammable - not combustible
 Relative density : No data available
 Solubility : No data available
 Partition coefficient : No data available
 Auto-ignition temperature : No data available

Hydrogen Sulfide (0.0001%-0.05%) in Air (Oxygen 20.9% bal. Nitrogen)

Decomposition temperature : No data available
 Viscosity : Not applicable

| | Hydrogen Sulfide | Oxygen | Nitrogen | |
|--------------------------|------------------|----------------------------|----------------------------|--|
| Molecular weight (grams) | 34.08 | 32.00 | 28.013 | |
| Boiling point | -60.3 °C | -182.9 °C | -196 °C | |
| Vapor pressure | 18100 hPa@20 °C | Above critical temperature | Above critical temperature | |
| Vapor density at 20°C | 1.19 | 1.11 | 0.97 | |
| Relative gas density | 1.427 | 1.331 | 1.153 | |
| Critical Temperature | 100.5 °C | -118.6 °C | -146.9 °C | |

Section 10. STABILITY AND REACTIVITY

10.1. Reactivity

No reactivity hazard other than the effects described below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.4. Conditions to avoid

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

None known

Section 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Nitrogen (7727-37-9)

LC50 inhalation rat (ppm) 410,000 ppm/4 hours

Oxygen (7782-44-7)

LC50 inhalation rat (ppm) 400,000 ppm/4 hours

Hydrogen Sulfide (7783-06-4)

LC50 inhalation rat (ppm) 712 ppm/1h

LC50 inhalation rat (ppm) 444 ppm/4h

11.1. Information on routes of exposure

Hydrogen Sulfide (0.0001%-0.05%) in Air (Oxygen 20.9% bal. Nitrogen)

| | |
|--------------|---|
| Inhalation | : Adverse effects not expected from this product |
| Skin contact | : Adverse effects not expected from this product |
| Eye contact | : May cause irritation. Ocular toxicity has been reported at hydrogen sulfide concentrations ranging from 5-30 ppm. |
| Ingestion | : Ingestion is not considered a potential route of exposure |

11.2. Symptoms related to physical, chemical and toxicological characteristics

| | |
|----------|---|
| Symptoms | Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere (<=18%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death. Hydrogen sulfide gas between 15-500 ppm can cause headache, nausea and dizziness. continued exposure at these levels can lead to loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. |
|----------|---|

11.3. Delayed and immediate effects

| | |
|--|---|
| Skin corrosion/irritation | : Contact with rapidly expanding gas may cause burns or frostbite. Concentrations of 50-500ppm (hydrogen sulfide) cause eye and respiratory irritation. |
| Serious eye damage/irritation | : Contact with rapidly expanding gas may cause burns or frostbite. |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| Developmental Toxicity | : Not classified |
| Specific target organ toxicity (single exposure) | : Not classified |
| Specific target organ toxicity (repeated exposure) | : Not classified |
| Aspiration hazard | : Not classified Not applicable for gases and gas-mixtures |

11.4. Carcinogenic effects

The components of this material are not found on the following lists: FEDERAL OSHA Z LIST, NTP AND IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

Section 12. ECOLOGICAL INFORMATION

12.1. Aquatic Toxicity

Hydrogen Sulfide (7783-06-4)

| | |
|------------|--|
| Fish | 0.448: 96 hours <i>Lepomis macrochirus</i> mg/L LC50 flow-through 0.016: 96 hours <i>Pimephales promelas</i> mg/L LC50 flow-through. |
| Crustacean | 0.022: 96 hours <i>Gammarus pseudolimnaeus</i> mg/L LC50 |

12.2. Persistence and degradability

No information available for the product

12.3. Bioaccumulative potential

Hydrogen Sulfide (7783-06-4)

Partition coefficient 0.45

12.4. Mobility in soil

No information available for the product

12.5. Other





No information available for the product

Section 13. DISPOSAL CONSIDERATIONS

13.1. Disposal methods

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14. TRANSPORTATION INFORMATION

| | US DOT | TDG | IMDG | IATA |
|-----------------------------------|---|---|--|---|
| UN # | UN 1956 | UN 1956 | UN 1956 | UN 1956 |
| Proper shipping name | Compressed gas, n.o.s. (Nitrogen, Oxygen) | Compressed gas, n.o.s. (Nitrogen, Oxygen) | Compressed gas, n.o.s. (Nitrogen, Oxygen) | Compressed gas, n.o.s. (Nitrogen, Oxygen) |
| Transport hazard class(es) | 2.2  | 2.2  | 2.2  | 2.2  |
| Packing group | - | - | - | - |
| Environment | No. | No. | No. | No. |

Section 15. REGULATORY INFORMATION

15.1. US Federal regulations

SARA 311/312 hazard categories

Acute Health : No
 Chronic Health : No
 Fire : No
 Pressure : Yes
 Reactive : No

SARA Title III Notifications and Information: None known

This product does not contain toxic chemicals subject to reporting requirements of section 313 of the Emergency planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

SARA 311/312 Sudden Release of Pressure Hazard

15.2. US State regulations

| |
|--|
| Nitrogen (007727-37-9) |
| U.S. - Massachusetts - Right To Know List |
| U.S. - Minnesota - Right To Know Hazardous Substance List |
| U.S. - New Jersey - Right To Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right To Know) List |
| Oxygen (007782-44-7) |
| U.S. - Massachusetts - Right To Know List |
| U.S. - New Jersey - Right To Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right To Know) List |
| Hydrogen Sulfide (7783-6-4) |
| U.S. - Massachusetts - Right To Know List |
| U.S. - New Jersey - Right To Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right To Know) List |

Section 16. OTHER INFORMATION

Date of issue/Date of revision 11/1/2023

Revision Note

Hazardous Material Information System (USA)

| | |
|------------------|--|
| Hazard Scale | : 0 = Minimal/ 1 = Slight/ 2 = Moderate/ 3 = Serious/ 4 = Severe |
| Health | : 0 |
| Fire | : 0 |
| Physical hazards | : 3 |

Key/Legend

| | |
|--------|---|
| SARA | Superfund Amendments and Reauthorization Act |
| OSHA | Occupational Safety and Health Administration |
| DOT | Department of Transportation |
| TSCA | Toxic Substance Control Act |
| NTP | National Toxicology Program |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| PEL | Permissible Exposure Limit |
| STEL | Short Term Exposure Limit |
| TLV | Threshold Limit Value |
| TDG | Transportation of Dangerous Goods |
| CAS | Chemical Abstracts Service |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| TWA | Time Weighted Average |
| Prop | Proposition |
| ATE | Acute Toxicity Estimate |



Hydrogen Sulfide (0.0001%-0.05%) in Air (Oxygen 20.9% bal. Nitrogen)

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose (s).