

Issue dateMarch 1, 2015Reviewed dateNovember 1, 2023

# **Safety Data Sheet**

	SDS ID# 5030	
Section 1. IDENTIFICATION		
1.1. Product identifier		
Product form	: Mixture	
Product name	: Nitrogen Dioxide (0.0001%-0.02%) in Air (Oxygen 20.9% bal. Nitrogen)	

: Calibration gas/Bumptest gas/Function test gas

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use

# 1.3. Details of the supplier of the safety data sheet

Intermountain Specialty Gases 21913 Cobalt Ave. Caldwell, Idaho 83605 Telephone 1-208-585-5829 or Toll free 1-800-552-5003 www.isgases.com

# **1.4. Emergency telephone number**Emergency number: CHEMTREC: 1-800-424-9300

Section 2. HAZARDS INDEN	TIFICATION
2.1. Classification of the sub	stance or mixture
Classification	: GASES UNDER PRESSURE - Compressed gas
2.2. Label elements	
Hazard pictograms	
Signal word	: WARNING
Hazard statements	: H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED : CGA-HG24 - MAY SUPPORT COMBUSTION : OSHA - PG01 - DO NOT REMOVE THIS PRODUCT LABEL
Precautionary statements	
[General]	: Read and follow all Safety Data Sheets (SDS's) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have a product container or label at hand. Use equipment rated for cylinder pressure.



: P202 - Do not handle until all safety precautions have been read and understood : P271+P403- Use only outdoors or in a well-ventilated area
: P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. : P313 - Get medical advice/attention.
: CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
: Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

#### **2.3. Other hazards** No additional information available

2.4. Unknown acute toxicity

No data available

# Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	%
Nitrogen	(CAS No) 7727-37-9	76.48 -80.4999
Oxygen	(CAS No) 7782-44-7	19.49 - 23.5
Nitrogen Dioxide	(CAS No) 10102-44-0	0.0001 - 0.02

Section 4. FIRST AID MEASU	IRES
4.1. Description of first aid n	neasures
General	: IF exposed or concerned: Get medical advice/attention.
Inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. If
	breathing has stopped, give artificial respiration or oxygen by trained personnel. If
	victim feels unwell, seek medical advice.
Skin contact	: Immediately flush with copious amount of water for at least 15 minutes.
Eye contact	: Immediately flush with copious amount of water for at least 15 minutes.
Ingestion	: Ingestion is not considered a potential route of exposure, refer to the inhalation
	section.
4.2. Most important sympto	oms/effects, acute and delayed
Acute	
Inhalation	: Adverse effects not expected from this product.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Ingestion	: Ingestion is not considered a potential route of exposure, refer to the inhalation
	section.
Frostbite	: Thaw frosted parts with lukewarm water. Do not rub affected areas. Get immediate
EN (English US)	SDS ID# 5030 Page 2 of



	medical advice/attention.
Symptoms/injuries upon intravenous	: Symptoms of overexposure are dizziness, headache, tiredness, nausea,
administration	unconsciousness, cessation of breathing.
Chronic symptoms	: Adverse effects not expected from this product.
Delayed	: Adverse effects not expected from this product.

### 4.3. Indication of any immediate medical attention and special treatment needed

If victim feels unwell, seek medical advice. If breathing is difficult, give artificial respiration or oxygen by trained personnel.

Section 5. FIREFIGHTING MEASURES 5.1. Extinguishing media	
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None known
5.2. Special hazards arising from the s	ubstance or mixture
Fire hazard	: The product is not flammable
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing
	risk of burns and injuries.
Reactivity	: None known.
5.3. Advice for fire-fighters	
Firefighting instructions	: In case of fire: Evacuate all personnel from the danger area. Stop the leak and flow of gas before extinguishing fire, if safe to do so. If this is not possible, withdraw from area and allow fire to burn. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Let the fire burn. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus, SCBA) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

Section 6. ACCIDENTAL RELEASE MEASURES		
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Ensure adequate ventilation.	
6.1.1. For non -emergency persor	nel	
Protective equipment	: Wear protective equipment consistent with the site emergency plan.	
Emergency procedures	: Escape the danger area by the closest safe route. Close doors and windows of	
	adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying	
	areas. Keep upwind.	
6.1.12. For emergency responder	S	
Protective equipment	: Standard protective clothing and equipment (e.g., Self Contained Breathing	
	Apparatus) for fire fighters. Equip cleanup crew with proper protection.	
Emergency procedures	: Evacuate and limit access. Ventilate area. See information above "For non-	
	emergency personnel".	
6.2. Methods and material for co	ntainment and cleaning up	



For containment	: Immediately contact emergency personnel. Try to stop gas leak if safe to do so.
Methods for cleaning up	:Dispose of content and/or container in accordance with local, regional, national,
	and/or international regulations.
Section 7. HANDLING AND STORAG	Ε
7.1. Precautions for safe handling	
Precautions for safety handling	: Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Protect cylinders from physical damage; do not drag, roll, slide, or drop.
Hygiene measures	: Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, incl	uding any incompatibilities
Technical measures	: None known.
Storage conditions	: Do not expose to temperatures exceeding 52°C (125°F). Store locked up. Keep containers closed when not in use. Protect cylinder from physical damage. Store and use away from heat, sparks, open flame or any other ignition source. Store in well ventilated area.
Incompatible products	: None known.
Incompatible materials	: None known.
·	

## Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OSHA PEL		Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV
		(as of 4/26/13)	(as of 4/26/13)	
	mg/m <sup>3</sup>	8-hour TWA	up to 10-hour TWA	8-hour TWA
ppm	mg/m	(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling
Not established	Not established	Not established	Not established	Simple asphyxiar
xygen (7782-44-7)				
OSHA PEL		Cal/OSHA PEL	NIOSH REL	
OSH	A PEL			ACGIH 2015 TLV
OSH		(as of 4/26/13)	(as of 4/26/13)	ACGIH 2015 TLV
	-			ACGIH 2015 TLV 8-hour TWA
OSH. ppm	mg/m <sup>3</sup>	(as of 4/26/13)	(as of 4/26/13)	
	-	(as of 4/26/13) 8-hour TWA	(as of 4/26/13) up to 10-hour TWA	8-hour TWA
ppm	mg/m <sup>3</sup>	(as of 4/26/13) 8-hour TWA (ST) STEL ( C ) Ceiling	(as of 4/26/13) up to 10-hour TWA (ST) STEL	8-hour TWA (ST) STEL ( C ) Ceiling

Cal/OCHA DEI



0517	4 F 66			ACGIH 2015 TLV
		(as of 4/26/13)	(as of 4/26/13)	
222	mg/m <sup>3</sup>	8-hour TWA	up to 10-hour TWA	8-hour TWA
ppm	mg/ m	(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling
$(C) \in nnm$	( C ) 9 mg/m <sup>3</sup>	(ST) 1 ppm	(ST) 1 ppm	0.2 ppm
( C ) 5 ppm				

### 8.2. Appropriate engineering controls

Engineering measures/controls

: Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly check for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may me released. Consider work permit system e.g. for maintenance activities.

8.3. Individual protection measures	
Hand protection	: Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.gLab coats, coveralls or flame resistant clothing.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved
	standard if a risk assessment indicates this is necessary.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section
	13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection

Section 9. PHYSICAL AND CHEMICAL PROPERTIES		
9.1. Exposure controls		
Appearance	: Compressed gas	
Physical state	: Gas	
Color	: Reddish-brown in air.	
Odor	: Acrid	
Odor threshold	: 0.1 - 0.4 ppm	
рН	: No data available	
Freezing point	: No data available	
Flash point	: No data available	
Evaporation rate	: No data available	
Flammability (solid, gas)	: Not Flammable - not combustible	
Upper flammability	: Not Flammable - not combustible	
Lower flammability	: Not Flammable - not combustible	
Relative density	: No data available	
Solubility	: No data available	
Partition coefficient	: No data available	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	



	Nitrogen Dioxide	Oxygen	Nitrogen	
Molecular weight (grams)	46.01	32.00	28.013	
Boiling point	21.1 °C	-182.9 °C	-196 °C	
Vapor pressure	14.8 psia@STP	Above critical temperature	Above critical temperature	
Vapor density at 20°C	2.8	1.11	0.97	
Relative gas density	3.4	1.331	1.153	
Critical Temperature	158.2 °C	-118.6 °C	-146.9 °C	

#### Section 10. STABILITY AND REACTIVITY

**10.1. Reactivity** 

Viscosity

No reactivity hazard other than the effects described below.

**10.2.** Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

: Not applicable

10.4. Conditions to avoid

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**10.5.** Incompatible materials

Sulfur dioxide is not compatible with strong bases, strong oxidizers, powdered metals, metal oxides, interhalogens, metal acetylides, sodium hydride, silver azide, cesium azide, fluorine, zinc, zinc compounds.

**10.6. Hazardous decomposition products** 

Strong oxidizing agents. Combustible materials. Organic material.

#### Section 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Nitrogen (7727-37-9)	
LC50 inhalation rat (ppm)	410,000 ppm/4 hours
Oxygen (7782-44-7)	
LC50 inhalation rat (ppm)	400,000 ppm/4 hours
Nitrogen dioxide (10102-44-0)	
LC50 inhalation rat (ppm)	115 ppm / 1 hour
(1-1)	
11.1. Information on routes of e	xposure

Inhalation

: Adverse effects not expected from this product



Skin contact	: Adverse effects not expected from this product
Eye contact	: May cause irritation.
Ingestion	: Ingestion is not considered a potential route of exposure

11.2. Symptoms related to physical, chemical and toxicological characteristics		
Symptoms	: No information available	
11.3. Delayed and immediate effects	S	
Skin corrosion/irritation	: Contact with rapidly expanding gas may cause burns or frostbite. Concentrations of	
	10-20 ppm Nitrogen dioxide are mildly irritating to the skin.	
Serious eye damage/irritation	: Contact with rapidly expanding gas may cause burns or frostbite. Concentrations of	
	10-20 ppm Nitrogen dioxide are mildly irritating to the eyes.	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: This product does not contain any carcinogens or potential carcinogens listed by	
	OSHA, IARC or NTP.	
Reproductive toxicity	: Not classified	
Developmental Toxicity	: Not classified	

exposure)	
Specific target organ toxicity (repeated	: Repeated overexposure to Nitrogen dioxide may cause respiratory problems,
exposure)	fatigue, alteration to taste and smell, dental erosion and gum disease.
Aspiration hazard	: Not classified
	Not applicable for gases and gas-mixtures

: Respiratory system, eyes, skin

#### **11.4. Carcinogenic effects**

Specific target organ toxicity (single

The components of this material are not found on the following lists: FEDERAL OSHA Z LIST, NTP AND IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

#### Section 12. ECOLOGICAL INFORMATION

#### **12.1. Aquatic Toxicity**

No information available for the product

#### 12.2. Persistence and degradability

No information available for the product

#### **12.3.** Bioaccumulative potential

No information available for the product

#### 12.4. Mobility in soil

No information available for the product

#### 12.5. Other

No information available for the product



#### Section 13. DISPOSAL CONSIDERATIONS

### 13.1. Disposal methods

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14. TRANSPORATION INFORMATION

	US DOT	TDG	IMDG	ΙΑΤΑ
UN #	UN 1956	UN 1956	UN 1956	UN 1956
Proper shipping name	Compressed gas, n.o.s. (Nitrogen, Oxygen)			
		(		
Transport hazard class(es)	2.2 INN FLAMMABLE GAS	2.2 NON-FLAMMABLE GAS	2.2 INCH-FLAMMABLE GAS	2.2 ROH-FLAMMABLE GAS
Packing group	-	-	-	-
Environment	No.	No.	No.	No.

#### Section 15. REGULATORY INFORMATION

**15.1. US Federal regulations** 

#### SARA 311/312 hazard categories

Acute Health	: Yes	
Chronic Health	: No	
Fire	: No	
Pressure	: Yes	
Reactive	: No	
SARA Title III Notifications a	nd Information: None known	
	• •	ting requirements of section 313 of the Emergency planning
and Community Right-To-Ki	now Act (EPCRA) of 1986 and of 40	CFR 372.
SARA 311/312	Sudden Release of Pr	essure Hazard

### **15.2. US State regulations**

litrogen (007727-37-9)	
J.S Massachusetts - Right To Know List	
J.S Minnesota - Right To Know Hazardous Substance List	
J.S New Jersey - Right To Know Hazardous Substance List	
J.S Pennsylvania - RTK (Right To Know) List	
Dxygen (007782-44-7)	
J.S Massachusetts - Right To Know List	
J.S New Jersey - Right To Know Hazardous Substance List	
J.S Pennsylvania - RTK (Right To Know) List	



Nitrogen dioxide (10102-44-0)	
U.S Massachusetts - Right To Know List	
U.S New Jersey - Right To Know Hazardous Substance List	
U.S Pennsylvania - RTK (Right To Know) List	

Section 16. OTHER INFORMATION	
Date of issue/Date of revision	11/1/2023
Revision Note	
Hazardous Material Information Sy	rstem (USA)
Hazard Scale	: 0 = Minimal/ 1 = Slight/ 2 = Moderate/ 3 = Serious/ 4 = Severe
Health	:1
Fire	: 0
Physical hazards	: 3
	—

Key/Legend	
SARA	Superfund Amendments and Reauthorization Act
OSHA	Occupational Safety and Health Administration
DOT	Department of Transportation
TSCA	Toxic Substance Control Act
NTP	National Toxicology Program
ACGIH	American Conference of Governmental Industrial Hygienists
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TDG	Transportation of Dangerous Goods
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
TWA	Time Weighted Average
Prop	Proposition
ATE	Acute Toxicity Estimate

#### **DISCLAIMER OF EXPRESSED AND IMPLIED WARRATIES**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose (s).