

Hydrogen Sulfide (0.0001%-0.01%); Methane (0.0001%-3.0%) in Nitrogen

Issue dateMarch 1, 2015Reviewed dateNovember 1, 2023

Safety Data Sheet

	SDS ID# 5082		
Section 1. IDENTIFICATION			
1.1. Product identifier			
Product form	: Mixture		
Due du et a sur e			
Product name	: Hydrogen Sulfide (0.0001%-0.01%); Methane (0.0001%-3.0%) in Nitrogen		

: Calibration gas/Bumptest gas/Function test gas

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use

1.3. Details of the supplier of the safety data sheet

Intermountain Specialty Gases 21913 Cobalt Ave. Caldwell, Idaho 83605 Telephone 1-208-585-5829 or Toll free 1-800-552-5003 www.isgases.com

1.4. Emergency telephone numberEmergency number: CHEMTREC: 1-800-424-9300

Section 2. HAZARDS INDENTIFICATION			
2.1. Classification of the	substance or mixture		
Classification	: GASES UNDER PRESSURE - Compressed gas		

2.2. Label elements		
Hazard pictograms		
Signal word	: WARNING	
Hazard statements	: H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED : CGA-HG24 - MAY SUPPORT COMBUSTION : OSHA - PG01 - DO NOT REMOVE THIS PRODUCT LABEL	
Precautionary statements		
[General]	: Read and follow all Safety Data Sheets (SDS's) before use. Read label before use out of reach of children. If medical advice is needed, have a product container or hand. Use equipment rated for cylinder pressure.	•
EN (English US)	SDS ID# 5082	Page 1 of 10



[Prevention]	: P202 - Do not handle until all safety precautions have been read and understood : P271+P403- Use only outdoors or in a well-ventilated area
[Response]	: P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
[Storage]	: CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
[Disposal]	: Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

No data available

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%
Nitrogen	(CAS No) 7727-37-9	73.49 - 80.5098
Oxygen	(CAS No) 7782-44-7	19.5 - 23.5
Methane	(CAS No) 74-82-8	0.0001 - 3.0
Hydrogen Sulfide	(CAS No) 7783-06-4	0.0001 - 0.01

Section 4. FIRST AID MEASURES	
4.1. Description of first aid measures	
General	: IF exposed or concerned: Get medical advice/attention.
Inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. If
	breathing has stopped, give artificial respiration or oxygen by trained personnel. If victim feels unwell, seek medical advice.
Skin contact	: Immediately flush with copious amount of water for at least 15 minutes.
Eye contact	: Immediately flush with copious amount of water for at least 15 minutes.
Ingestion	: Ingestion is not considered a potential route of exposure, refer to the inhalation
	section.
4.2. Most important symptoms/effect	ts, acute and delayed
Acute	
Inhalation	: Adverse effects not expected from this product.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Ingestion	: Ingestion is not considered a potential route of exposure, refer to the inhalation



Frostbite	section. : Thaw frosted parts with lukewarm water. Do not rub affected areas. Get immediate medical advice/attention.
Symptoms/injuries upon intravenous administration	: Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing.
Chronic symptoms Delayed	: Adverse effects not expected from this product. : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If victim feels unwell, seek medical advice. If breathing is difficult, give artificial respiration or oxygen by trained personnel.

Section 5. FIREFIGHTING MEASURES	
5.1. Extinguishing media	
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None known
5.2. Special hazards arising from the s	ubstance or mixture
Fire hazard	: The product is not flammable
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity	: None known.
5.3. Advice for fire-fighters	
Firefighting instructions	: In case of fire: Evacuate all personnel from the danger area. Stop the leak and flow of gas before extinguishing fire, if safe to do so. If this is not possible, withdraw from area and allow fire to burn. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Let the fire burn. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus, SCBA) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.
Section 6. ACCIDENTAL RELEASE MEA	SURES
6.1. Personal precautions, protective of	equipment and emergency procedures
General measures	: Ensure adequate ventilation.
6.1.1. For non -emergency personnel	

6.1.1. For non-emergency personner	
Protective equipment	: Wear protective equipment consistent with the site emergency plan.
Emergency procedures	: Escape the danger area by the closest safe route. Close doors and windows of
	adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying
	areas. Keep upwind.
6.1.12. For emergency responders	
Protective equipment	: Standard protective clothing and equipment (e.g., Self Contained Breathing
	Apparatus) for fire fighters. Equip cleanup crew with proper protection.
Emergency procedures 6.1.12. For emergency responders	 : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind. : Standard protective clothing and equipment (e.g., Self Contained Breathing



Emergency procedures	: Evacuate and limit access. Ventilate area. See information above "For non- emergency personnel".	
6.2. Methods and material for conta	inment and cleaning up	
For containment	: Immediately contact emergency personnel. Try to stop gas leak if safe to do so.	
Methods for cleaning up	:Dispose of content and/or container in accordance with local, regional, national,	
	and/or international regulations.	
Section 7. HANDLING AND STORAG	Ε	
7.1. Precautions for safe handling		
Precautions for safety handling	: Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Protect cylinders from physical damage; do not drag, roll, slide, or drop.	
Hygiene measures	: Do not eat, drink or smoke when using this product.	
7.2. Conditions for safe storage, incl	uding any incompatibilities	
Technical measures	: None known.	
Storage conditions	: Do not expose to temperatures exceeding 52°C (125°F). Keep containers closed	
	when not in use. Protect cylinder from physical damage. Store in well ventilated area.	
Incompatible products	: None known.	
Incompatible materials	: None known.	

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Nitrogen (7727-37-9)				
OSHA PEL		Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV
ppm	mg/m ³	(as of 4/26/13)	(as of 4/26/13)	
		8-hour TWA	up to 10-hour TWA	8-hour TWA
		(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling
Not established	Not established	Not established	Not established	Simple asphyxiant

Oxygen (7782-44-7)

OSHA PEL		Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV
ppm	mg/m ³	(as of 4/26/13)	(as of 4/26/13)	
		8-hour TWA	up to 10-hour TWA	8-hour TWA
		(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling

There are no specific exposure limits for Nitrogen. Nitrogen is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.



Methane (74-82-8)							
OSHA PEL			Cal/OSHA PEL	NIOSH REL		ACGIH 2015 TLV	
			(as of 4/26/13)	(as of 4/26/13)			
nr	m	mg/m ³	8-hour TWA	up to 10-ho	ur TWA	8-hou	r TWA
PF	om	mg/m	(ST) STEL	(ST) ST	EL	(ST)	STEL
			(C) Ceiling	(C) Cei	ing	(C)(Ceiling
						1,000) ppm
Hydrogen	Sulfide (7783	-06-4)			-		
		OSHA	PELs	Cal/OSHA PEL	NIOSH	REL	ACGIH
Accepta		ceptable maximum peak	(as of 4/26/13)	(as of 4/2	26/13)	2015 TLV	
8-hour Time	Acceptable				up to 10-ho	our TWA	8-hour
Weighted Average	Ceiling Concentration	Ceiling	Maximum Duration	8-hour TWA	(ST) S	TEL	TWA
(TWA)		Concentration Concentration		(ST) STEL	(C) Ce	eiling	(ST) STEL
				(C) Ceiling	IDLI	Н	(C)
	10 min once only if no o		10 min once only if no other	10 ppm			1 ppm
	20 ppm	0 nnm = 50 nnm = 1	measurable exposure occurs.	(ST) 15 ppm	(C) 10 ppm	[10 min]	(ST) 5 ppm
				(C) 20 ppm	IDLH - 100 ppm		

8.2. Appropriate engineering controls Engineering measures/controls : Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly check for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may me released. Consider work permit system e.g. for maintenance activities.

8.3. Individual protection measures	
Hand protection	: Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.gLab coats, coveralls or flame resistant clothing.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved
	standard if a risk assessment indicates this is necessary.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section
	13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection

Section 9. PHYSICAL AND CHEMICAL PROPERTIES		
9.1. Exposure controls		
Appearance	: Clear, colorless gas.	
Physical state	: Gas	
Color	: Colorless	
EN (English US)	SDS ID# 5082	Page 5 of 10



Odor	: Rotten eggs: Sulfide-like
Odor threshold	: 0.13 ppm (Hydrogen sulfide)
рН	: No data available
Freezing point	: No data available
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: Not Flammable - not combustible
Upper flammability	: Not Flammable - not combustible
Lower flammability	: Not Flammable - not combustible
Relative density	: No data available
Solubility	: No data available
Partition coefficient	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: Not applicable

	Oxygen	Nitrogen	Methane	Hydrogen Sulfide
Molecular weight (grams)	32.00	28.013	16.04	34.08
Boiling point	-182.9 °C	-196 °C	-161.49 °C	-60.3 °C
Vapor pressure	Above critical	Above critical	Above critical	18100 hPa@20 °C
	temperature	temperature	temperature	18100 1178@20 C
Vapor density at 20°C	1.11	0.97	0.56	1.19
Relative gas density	1.331	1.153	0.6784	1.427
Critical Temperature	-118.6 °C	-146.9 °C	-82.10 °C	100.5 °C

Section 10. STABILITY AND REACTIVITY

10.1. Reactivity

No reactivity hazard other than the effects described below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.4. Conditions to avoid

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. TOXICOLOGICAL INFORMATION



Acute toxicity

Nitrogen (7727-37-9)	
	410,000 ppm/4h
Oxygen (7782-44-7)	
LC50 inhalation rat (ppm)	400,000 ppm/4h
Hydrogen Sulfide (7783-06-4)	
	712 ppm/1h
	444 ppm/4h
11.1. Information on routes of exposure	e
	Adverse effects not expected from this product
	: Adverse effects not expected from this product
	: May cause irritation. Ocular toxicity has been reported at hydrogen sulfide
•	concentrations ranging from 5-30 ppm.
Ingestion	: Ingestion is not considered a potential route of exposure
11.2. Symptoms related to physical, che	
	Hydrogen sulfide gas between 15-500 ppm can cause headache, nausea and
	dizziness. continued exposure at these levels can lead to loss of reasoning and
	balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness.
11.3. Delayed and immediate effects	
Skin corrosion/irritation	: Contact with rapidly expanding gas may cause burns or frostbite. Concentrations of
	: Contact with rapidly expanding gas may cause burns or frostbite. Concentrations of 50-500ppm (hydrogen sulfide) cause eye and respiratory irritation.
Serious eye damage/irritation	50-500ppm (hydrogen sulfide) cause eye and respiratory irritation.
Serious eye damage/irritation Respiratory or skin sensitization	50-500ppm (hydrogen sulfide) cause eye and respiratory irritation. : Contact with rapidly expanding gas may cause burns or frostbite.
Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity	50-500ppm (hydrogen sulfide) cause eye and respiratory irritation.: Contact with rapidly expanding gas may cause burns or frostbite.: Not classified
Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity	50-500ppm (hydrogen sulfide) cause eye and respiratory irritation.: Contact with rapidly expanding gas may cause burns or frostbite.: Not classified: Not classified
Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity	 50-500ppm (hydrogen sulfide) cause eye and respiratory irritation. : Contact with rapidly expanding gas may cause burns or frostbite. : Not classified : Not classified : Not classified
Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity Developmental Toxicity	 50-500ppm (hydrogen sulfide) cause eye and respiratory irritation. : Contact with rapidly expanding gas may cause burns or frostbite. : Not classified : Not classified : Not classified : Not classified
Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity Developmental Toxicity Specific target organ toxicity (single	 50-500ppm (hydrogen sulfide) cause eye and respiratory irritation. Contact with rapidly expanding gas may cause burns or frostbite. Not classified
Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity Developmental Toxicity Specific target organ toxicity (single exposure)	 50-500ppm (hydrogen sulfide) cause eye and respiratory irritation. Contact with rapidly expanding gas may cause burns or frostbite. Not classified
Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity Developmental Toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Aspiration hazard	 50-500ppm (hydrogen sulfide) cause eye and respiratory irritation. Contact with rapidly expanding gas may cause burns or frostbite. Not classified

11.4. Carcinogenic effects

The components of this material are not found on the following lists: FEDERAL OSHA Z LIST, NTP AND IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

Section 12. ECOLOGICAL INFORMATION



12.1. Aquatic Toxicity

Ecology - general

: No ecological damage caused by this product

Hydrogen Sulfide (7783-06-4)	
Fish	0.448: 96 hours Lepomis macrochirus mg/L LC50 flow-through 0.016: 96 hours
	Pimephales promelas mg/L LC50 flow-through.
Crustacean	0.022: 96 hours Gammarus pseudolimnaeus mg/L LC50

12.2. Persistence and degradability

No information available for the product

12.3. Bioaccumulative potential	
Hydrogen Sulfide (7783-06-4)	
Partition coefficient	0.45

12.4. Mobility in soil

No information available for the product

12.5. Other

No information available for the product

Section 13. DISPOSAL CONSIDERATIONS

13.1. Disposal methods

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14. TRANSPORATION INFORMATION

	US DOT	TDG	IMDG	ΙΑΤΑ
UN #	UN 1956	UN 1956	UN 1956	UN 1956
Proper shipping name	Compressed gas, n.o.s. (Nitrogen, Oxygen)			
Transport hazard class(es)	2.2 NON-FLAMMABLE GAS	2.2 NON-FLAMMABLE GAS	2.2 NON-FLAMMABLE GAS	2.2 NON FLAMMABLE GAS
Packing group	-	-	-	-
Environment	No.	No.	No.	No.

Section 15. REGULATORY INFORMATION

15.1. US Federal regulations

SARA 311/312 hazard categories

Acute Health



Hydrogen Sulfide (0.0001%-0.01%); Methane (0.0001%-3.0%) in Nitrogen

Chronic Health	: No	
Fire	: No	
Pressure	: Yes	
Reactive	: No	
SARA Title III Notifications	nd Information: None known	
This product does not cont	ain toxic chemicals subject to reporting requirements of sect	tion 313 of the Emergency planning
and Community Right-To-K	now Act (EPCRA) of 1986 and of 40 CFR 372.	
SARA 311/312	Sudden Release of Pressure Hazard	

15.2. US State regulations

Nitrogen (007727-37-9)
U.S Massachusetts - Right To Know List
U.S Minnesota - Right To Know Hazardous Substance List
U.S New Jersey - Right To Know Hazardous Substance List
U.S Pennsylvania - RTK (Right To Know) List
Oxygen (007782-44-7)
U.S Massachusetts - Right To Know List
U.S New Jersey - Right To Know Hazardous Substance List
U.S Pennsylvania - RTK (Right To Know) List
Methane (000074-82-8)
U.S Massachusetts - Right To Know List
U.S Minnesota - Right To Know Hazardous Substance List
U.S New Jersey - Right To Know Hazardous Substance List
U.S Pennsylvania - RTK (Right To Know) List
Hydrogen Sulfide (7783-6-4)
U.S Massachusetts - Right To Know List
U.S New Jersey - Right To Know Hazardous Substance List
U.S Pennsylvania - RTK (Right To Know) List

Date of issue/Date of revision	11/1/2023
Revision Note	
Hazardous Material Information Sy	ystem (USA)
Hazard Scale	: 0 = Minimal/ 1 = Slight/ 2 = Moderate/ 3 = Serious/ 4 = Severe
Health	: 1
Fire	: 0
Physical hazards	: 3
Key/Legend	
SARA	Superfund Amendments and Reauthorization Act
OSHA	Occupational Safety and Health Administration

DOTDepartment of TransportatioTSCAToxic Substance Control Act



NTP	National Toxicology Program
ACGIH	American Conference of Governmental Industrial Hygienists
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TDG	Transportation of Dangerous Goods
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
TWA	Time Weighted Average
Prop	Proposition
ATE	Acute Toxicity Estimate

DISCLAIMER OF EXPRESSED AND IMPLIED WARRATIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose (s).